

CHARACTERISTICS

GENERAL DATA

Focusing Method	Electrostatic	
Deflection Method	Magnetic	
Deflection Angles (Approx.)		
Horizontal	102 Degrees	
Diagonal	114 Degrees	
Vertical	86 Degrees	
Phosphor	Aluminized P4	
Fluorescence	White	
Persistence	Short to Medium	
Faceplate	Bonded Shield	
(Gray Filter Glass Safety Plate Laminated Directly to Face of Tube)		
Light Transmittance of Faceplate Assembly (Approx.)	44 Percent	

ELECTRICAL DATA

Heater Voltage	6.3 Volts	
Heater Current	0.60 ±5% Ampere	
Heater Warm-up Time ¹	11 Seconds	
Direct Interelectrode Capacitances (Approx.)		
Cathode to All Other Electrodes	5 μmf	
Grid No. 1 to All Other Electrodes	6 μmf	
External Conductive Coating to Anode ²	1500 μmf	Max.
	1000 μmf	Min.

MECHANICAL DATA

Minimum Useful Screen Dimensions (Maximum Assured)		
Height	12 1/16 Inches	
Width	15 5/16 Inches	
Diagonal	17 3/4 Inches	
Area	174 Sq. Inches	
Neck Length	5 1/8 ± 1/8 Inches	
Overall Length	12 3/8 ± 5/16 Inches	
Bulb	C149 Exp. #5 or Equiv.	
Safety Plate	FP159A	
Bulb Contact (Recessed Small Cavity Cap)	J1-21	
Base	B7-208	
Basing	8HR	
Weight (Approx.)	18 1/2 Pounds	



RATINGS

MAXIMUM RATINGS (Design Maximum Values) Grid Drive Service

Maximum Anode Voltage	20,000 Volts	dc
Minimum Anode Voltage	12,000 Volts	dc
Grid No. 4 Voltage (Focusing Electrode)	-550 to +1100 Volts	dc
Grid No. 2 Voltage	550 Volts	dc
Grid No. 1 Voltage		
Negative Bias Value	155 Volts	dc
Negative Peak Value	220 Volts	
Positive Bias Value	0 Volts	dc
Positive Peak Value	2 Volts	
Peak Heater-Cathode Voltage		
Heater Negative with Respect to Cathode		
During Warm-up Period not to Exceed 15 Seconds	450 Volts	
After Equipment Warm-up Period	200 Volts	
Heater Positive with Respect to Cathode	200 Volts	

QUICK REFERENCE DATA

- Television Picture Tube
- 19" Direct Viewed
- Rectangular Glass Type
- Spherical Faceplate
- Bonded Shield
- Gray Filter Glass
- Aluminized Screen
- Electrostatic Focus
- 114° Magnetic Deflection
- No Ion Trap
- External Conductive Coating



**SYLVANIA
ELECTRONIC TUBES**

A Division of
Sylvania Electric Products Inc.

**PICTURE TUBE OPERATIONS
SENECA FALLS, NEW YORK**

*Prepared and Released By The
TECHNICAL PUBLICATIONS SECTION
EMPORIUM, PENNSYLVANIA*

FEBRUARY, 1961

PAGE 1 OF 3

File Under
TELEVISION PICTURE TUBES

TYPICAL OPERATING CONDITIONS (Grid Drive Service)

Anode Voltage	16,000 Volts	dc
Grid No. 4 Voltage for Focus	0 to +400 Volts	dc
Grid No. 2 Voltage	300 Volts	dc
Grid No. 1 Voltage Required for Cutoff ³	-35 to -72 Volts	dc

CIRCUIT VALUES

Grid No. 1 Circuit Resistance	1.5 Megohms Max.
---	------------------

NOTES:

1. *Heater warm-up time is defined as the time required for the voltage across the heater to reach 80% of the rated heater voltage after applying four (4) times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to three (3) times the rated heater voltage divided by the rated heater current.*
2. *External conductive coating must be grounded.*
3. *Visual extinction of focused raster. Extinction of stationary focused spot will require that these values be about 5 volts more negative.*

WARNING:

X-ray radiation shielding may be necessary to protect against possible danger of personal injury from prolonged exposure at close range if this tube is operated at higher than the manufacturer's Maximum Rated Anode Voltage or 16,000 volts, whichever is less.

